



ELEVATION NOTES

- THIS DRAWING IS FOR DIAGRAMMATIC PURPOSES ONLY. FOR ACTUAL HANDING AND SWING, REFERENCE FLOOR PLANS.
- DIMENSIONS SHOWN FOR COORDINATION ONLY. EXACT LOCATIONS AND MOUNTING HEIGHTS TO BE FIELD COORDINATED WITH OWNER AND ARCHITECT.
- IF PLENUM INSTALLATION, CONDUIT IS NOT REQUIRED FOR THIS CABLE RUN.
- IF PLENUM INSTALLATION, STUB CONDUIT, w/PULL STRING, 6" ABOVE FINISHED CEILING.
- ALL CONDUIT IS 3/4" UNLESS OTHERWISE NOTED.
- FOR GROUTED DOOR FRAMES, PROVIDE CONDUIT INTO SPECIAL STEEL BOX OR STYROFOAM BLOCK TO FACILITATE BOTH INSTALLATION AND SERVICE.
- FIELD VERIFY ALL EXISTING INSTALLATION.
- ALL NEWLY INSTALLED ITEMS SHALL BE INSPECTED BY UNIVERSITY INSPECTOR.

GB-5

SINGLE DOOR, ALARMED/FREE EXIT
ELECTRIC LOCKSET w/REX SWITCH, LOCAL NOISE (SIREN & PIEZO)
ELEVATION

SCALE: N.T.S.

LBNL ELECTRICAL STANDARDS
SECURITY CARD ACCESS GB-5
SINGLE DOOR ALARMED/FREE EXIT MANUAL LOCKSET

UNIVERSITY OF CALIFORNIA LAWRENCE BERKELEY NATIONAL LABORATORY
FACILITIES DIVISION

DRAWN BY	DATE
CHECKED BY	
APPROVED BY	
CAD FILE PATH	
SCALE NTS	
DRAWING NO.	SHEET
SEC106A	GB-5
PROJECT NO.	